

Unleash the power of Boydur A10 and experience unmatched surface protection like never before. Our cutting-edge formula, backed by advanced technology, ensures exceptional results in both interior and exterior applications. Say goodbye to dusting, surface erosion, and compromised aesthetics. Say hello to a new era of surface protection.

Unrivaled Performance

Boydur A10 is a game-changer in the world of surface protection. With its MMA-based, solvent-free composition, it acts as the first line of defense, creating a shield that resists wear and tear. Our transparent, impregnating resin penetrates deep into the surface, eliminating dusting issues and preventing erosion. It brings out the natural texture, enhancing the vibrancy of colors and patterns, elevating the overall aesthetic appeal.

Effortless Application

We understand the importance of a seamless application process. That's why Boydur A10 is designed with simplicity in mind. Its single-component nature ensures hassle-free usage, while the air-drying feature allows for rapid curing in just one hour. With a wide range of compatible tools and techniques, you can achieve professional results effortlessly. Whether you choose to roll, brush, or spray, Boydur A10 adapts to your needs.

Unmatched Versatility

Boydur A10 is a true multi-purpose solution, suitable for a variety of applications. From military facilities to airports, industrial areas to historic landmarks, it offers unparalleled protection. Bridges, roads, residential complexes, and even healthcare facilities benefit from its remarkable performance. Wherever surfaces demand excellence, Boydur A10 stands strong, safeguarding against the harshest elements.

Beyond Expectations:

At Boydur, we take pride in exceeding expectations. Our commitment to quality is unmatched, ensuring longevity and durability. With an average consumption rate of 200-300 gr/m², every drop of Boydur A10 goes a long way, making it a cost-effective choice. Plus, its non-toxic and user-friendly nature makes it safe for both the environment and those involved in the application process.

Unlock the Potential:

Imagine surfaces that resist erosion, remain dustfree, and maintain their natural beauty over time. With Boydur A10, this vision becomes a reality. Take the leap towards unparalleled surface protection and unlock the true potential of your spaces. Discover the difference Boydur A10 can make.

Contact us today to learn more about Boydur A10 and explore how our innovative solution can revolutionize your surfaces.





Technical Specifications:

Form: Liquid

Color: Transparent

Consumption Rate: Average 200-300 gr/m2

Drying Time (20°C): Average 45-60 minutes

Minimum Application Temperature: 10°C

Shelf Life: 12 months in a dark and dry environment

at 20°C without opening the packaging

Packaging: 15 kg

Application: Preparation for Application: Required

Materials:

Roller and Brush: Use an appropriate amount according to the size of the surface to be applied.

Spray Machine: For very large areas, application can also be done using a spray machine compatible with single-component materials.

Boydur® S-90: Used for cleaning application tools.

Application:

The surface to be applied must be dry, clean, and sound during the application. Do not start the application without meeting these conditions.

Remove previously formed chalked areas by scraping them off.

Apply Boydur® A10 thinly onto the surface using a brush, roller, or spray machine. Wait for 1 hour for drying.

If the surface has been thoroughly impregnated by the first coat, apply subsequent coats. Wait for approximately 1 hour for each coat to dry.

Application tools can be cleaned with Boydur® S-90. It is recommended to perform the application from bottom to top.





"READY TO USE 1 HOUR AFTER THE APPLICATION!"



BOYTORUN KİMYA SANAYİ A.Ş.

i.E.T.T. Sitesi 3,Blok,D:1, 34467,Emirgan- İstanbul-TR. Tel: 0212 229 28 29-34, WhatsApp: 0542 437 9005 E-Mail: info@boytorun.com, Web: www.boytorun.com

